



OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Udayan Vihar -781171
Guwahati, Assam(India)
Email:oilmatpl@oilindia.in

OIL INDIA LIMITED invites Indigenous Competitive Bid through its e-Procurement portal <https://etender.srm.oilindia.in/sap/bc/gui/sap/its/bbpstart/>! For following e-tender :

e-Tender No and date	Materials Description	Bid Closing Date
SGI1332P14	Coating & Wrapping Material for Trunk Pipeline (Total 4 items)	09/01/2014
SGI1775P14	Lube Oil (Total 5 items)	09/01/2014

Application showing full address/email address with Tender Fee (Non-refundable) of Rs. 1,000.00 (Excepting PSUs and SSI units registered with NSIC) in favour of M/s Oil India Limited and payable at Guwahati is to be sent to Chief _Materials Manger Oil India Limited, P.O. Udayan Vihar , Assam-781171 .Application shall be accepted one week prior to Bid Closing date . The envelope containing the application for participation should clearly indicate “**REQUEST FOR ISSUE OF USER ID AND PASSWORD FOR E TENDER NO ...**” for easy identification and timely issue of user ID and password. On receipt of requisite tender fee, USER_ID and initial PASSWORD will be communicated to the bidder (through e-mail and ill be allo ed to participate in the tender through OIL’s e-Procurement portal. No physical tender documents will be provided. Details of NIT can be viewed using “Guest Login” provided in the e-Procurement portal. The link to e-Procurement portal has been also pro ided through OIL’s eb site www.oil-india.com.

Note : PSUs and SSI units are provided tender documents Free of Cost (as per govt guidelines), however they have to apply to OIL’s designated office to issue the tender documents before the last date of sale of tender document mentioned in the tender.



OIL INDIA LIMITED
(A Government of India Enterprises)
PO : Duliajan – 786602
Assam (India)

TELEPHONE NO. (91-374) 2808719

FAX NO: (91-374) 2800533

Email: tuhin_roy@oilindia.in ; erp_mm@oilindia.in

FORWARDING LETTER

Tender No. : SGI1332P14 dated 4/10/2013

Tender Fee : Rs 1,000.00

Bid Security Amount : Rs 13,39,000.00

Bidding Type : SINGLE STAGE TWO BID SYSTEM

Bid Closing on : As mentioned in the e-portal

Bid Opening on : -do-

Performance Security : Applicable

Integrity Pact : Applicable

OIL invites Bids for **Coating and Wrapping Material for Pipeline** through its e-Procurement site under **SINGLE STAGE TWO BID SYSTEM**. The bidding documents and other terms and conditions are available at Booklet No. MM/LOCAL/E-01/2005 for E-Procurement LCB Tenders. The prescribed Bid Forms for submission of bids are available in the Technical RFx -> External Area - > Tender Documents

The general details of tender can be viewed by opening the RFx [Tender] under RFx and Auctions.. The details of items tendered can be **found in the Item Data and details uploaded under Technical RFX.**

The tender will be governed by:

- a) “General Terms & Conditions” for e-Procurement as per Booklet No. MM/LOCAL/E-01/2005 for E-Procurement LCB Tenders and Amendment No. 1 to General Terms and Conditions for Indigenous E-Tender.
- b) Technical specifications and Quantity as per **Annexure – 1A**.
- c) The prescribed Bid Forms for submission of bids are available in the Technical RFx -> External Area - > Tender Documents.
- d) In the event of receipt of only a single offer against the tender within B.C. date, OIL reserves the right to extend the B.C. date as deemed fit by the Company. During the extended period, the bidders who have already submitted the bids on or before the original B.C. date, shall not be permitted to revise their quotation.
- e) Any sum of money due and payable to the contractor (including Security Deposit refundable to them) under this or any other contract may be appropriated by Oil India Limited and set-off against any claim of Oil India Limited (or such other person or persons

contracting through Oil India Limited) for payment of sum of money arising out of this contract or under any other contract made by the contractor with Oil India Limited (or such other person or persons contracting through Oil India Limited).

- f) Bidder are advised to fill up the Technical bid check list (**Annexure EEE**) and Response sheet (**Annexure FFF**) given in MS excel format in Technical RFx -> External Area -> Tender Documents. The above filled up document to be uploaded in the **Technical RFX Response**.

Special Note:

1.0 General Qualification Criteria:

In addition to the general BRC/BEC, following criteria on Bidders' Experience and their financial capabilities shall be considered (**documentary evidence to be provided along with the bid in Technical RFx -> External Area -> Tender Documents**) as on the Bid Closing Date:

- a) Bidder should have experience of successfully executing similar order of Rs **401.69 Lakhs** during last 3 years.
- b) Annual financial turnover of the firm in any of the last 3 financial years or current financial year should not be less than **Rs 1338.95 Lakhs**.

2.0 Application showing full address/email address with Tender Fee (Non-refundable) of Rs. 1,000.00 in favour of M/s Oil India Limited and payable at Guwahati is to be sent to Chief Material Manager , Oil India Limited (Pipeline Headquarter) , P.O. Udayan Vihar, Guwahati - 781171. Application shall be accepted only upto one week prior to the bid closing date (or as amended in e-portal). The envelope containing the application for participation should clearly indicate “REQUEST FOR ISSUE OF USER ID AND PASSWORD FOR E TENDER NO ...” for easy identification and timely issue of user ID and password. On receipt of requisite tender fee, USER_ID and initial PASSWORD will be communicated to the bidder (through e-mail) and will be allowed to participate in the tender through OIL's e- Procurement portal. No physical tender documents will be provided. Details of NIT can be viewed using “Guest Login” provided in the e-Procurement portal. The link to e-Procurement portal has been also provided through OIL's web site www.oil-india.com.

NOTE: PSUs and SSI units are provided tender documents Free of Cost (as per govt guidelines), however they have to apply to OIL's designated office to issue the tender documents before the last date of sale of tender document mentioned in the tender.

3.0 The tender is invited under SINGLE STAGE-TWO BID SYSTEM. The bidders are required to submit both the “TECHNO-COMMERCIAL UNPRICED BID” and “PRICED BID” through electronic format in the OIL's e-Tender portal within the Bid Closing Date and Time stipulated in the e-Tender.

3.1 Please ensure that Technical Bid / all technical related documents related to the tender are uploaded in the Technical RFx Response-> User -> Technical Bid only. The “TECHNO-COMMERCIAL UNPRICED BID” shall contain all techno-commercial details except the prices. Please note that no price details should be uploaded in Technical RFx Response.

3.2 The “PRICE BID” must contain the price schedule and the bidder's commercial terms and conditions. The prices of the items should be quoted in “Conditions Tab”. Details of prices as per Bid format / Commercial bid can be uploaded as Attachment under the attachment option under “Notes & Attachments”.

3.3 A screen shot in this regard is given below. Offer not complying with above submission procedure will be rejected as per Bid Rejection Criteria mentioned in Annexure-CCC.

Display RFX Response:

Go to this Tab “Technical RFX Response” for Uploading “Techno-commercial Unpriced Bid”.

Go to this Tab “Notes and Attachments” for Uploading “Priced Bid” files.

RFX Response Number 60006452 RFX Number TEST2 Status Submitted
RFX Owner WIPRO_TEST1 Total Value 0.00 INR RFX Response Version 1

Basic Data | Questions

Event Parameters

Currency: Indian Rupee

Detailed Price Information: Price with Conditions

Terms of Payment: 9010 90% against despatch+10% after receipt

Partners and Delivery Information

The table does not contain any data

On “EDIT” Mode- The following screen will appear. Bidders are advised to Upload “Techno-Commercial Unpriced Bid” and “Priced Bid” in the places as indicated above:

Edit RFX Response:

Bid on “EDIT” Mode

Area for uploading Techno-Commercial Unpriced Bid*

Area for uploading Priced Bid**

Submit | Read Only | Print Preview | Check | Technical RFX Response | Close | Save | Verify signature

RFX Response Number 60006452 RFX Number TEST2 Status Withdrawn Submission Deadline 13.04.2013 11:00:00 INDIA
RFX Owner WIPRO_TEST1 Total Value 0.00 INR RFX Response Version Number 2 RFX Version Number 5

RFX Information | Items | Notes and Attachments | Conditions | Summary

Notes

Add | Clear

Assigned To Category Text Preview

Attachments

Sign Attachment Add Attachment Edit Description Versioning Delete Create Qualification Profile

Assigned To Category Description File Name Version Processor Checked

The table does not contain any data

Note :

* The “Techno-Commercial Unpriced Bid” shall contain all techno-commercial details **except the prices.**

** The “Price bid” must contain the price schedule and the bidder’s commercial terms and conditions. For uploading Price Bid, first click on Sign Attachment, a browser window will open, select the file from the PC and click on Sign to sign the Sign. On Signing a new file with extension .SSIG will be created. Close that window. Next click on Add Attachment, a browser

window will open, select the .SSIG signed file from the PC and name the file under Description, Assigned to General Data and click on OK to save the File.

4.0 Please note that all tender forms and supporting documents are to be submitted through OIL's e-Procurement site only except following documents which are to be submitted manually in sealed envelope super scribed with **Tender no.** and **Due date to Chief Material Manager , Oil India Limited (Pipeline Headquarter), P.O. Udayan Vihar, Guwahati - 781171, Assam** on or before the Bid Closing Date and Time mentioned in the Tender.

- a) **Original Bid Security**
- b) **Detailed Catalogue (if any)**
- c) **Any other document required to be submitted in original as per tender requirement**

All documents submitted in physical form should be signed on all pages by the authorised signatory of the bidder and to be submitted in triplicate.

5.0 Bidders are requested to examine all instructions, forms, terms and specifications in the bid. Failure to furnish all information required as per the NIT or submission of offers not substantially responsive to the bid in every respect will be at the bidders risk and may result in rejection of its offer without seeking any clarifications.

6.0 Bidders must ensure that their bid is uploaded in the system before the tender closing date and time. Also, they must ensure that above documents which are to be submitted in a sealed envelope are also submitted at the above mentioned address before the bid closing date and time failing which the offer shall be rejected.

7.0 Bid must be submitted electronically only through OIL's e-procurement portal. Bid submitted in any other form will be rejected.

8.0 **SINGLE STAGE TWO BID SYSTEM** shall be followed for this tender and only the PRICED-BIDS of the bidders whose offers are commercially and technically acceptable shall be opened for further evaluation.

9.0 a) **The Integrity Pact is applicable against this tender.** OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide **Annexure-DDD** of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be returned by the bidder (along with the technical bid) duly signed (digitally) by the same signatory who signed the bid, i.e., who is duly authorized to sign the bid. Any bid not accompanied by Integrity Pact Proforma duly signed (digitally) by the bidder shall be rejected straightway. Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact has been signed by the bidder's authorized signatory who sign the Bid.

b) The name of the OIL's Independent External Monitors at present are as under:

- i) **SHRI N. GOPLASWAMI, I.A.S. (Retd.),**
Former Chief Election Commissioner of India
E-mail Id : gopalaswamin@gmail.com
- ii) **SHRI RAMESH CHANDRA AGARWAL, IPS (Retd.)**
Former Director General of Police
E-mail Id : rcagarwal@rediffmail.com

10.0 The tender shall be governed by the Bid Rejection & Bid Rejection Criteria given in enclosed **Annexure-CCC**. However, if any of the Clauses of the Bid Rejection Criteria / Bid Evaluation Criteria (as per **Annexure-CCC**) contradict the Clauses of the tender and / or “General Terms & Conditions” as per Booklet No. MM/LOCAL/E-01/2005 for E-procurement (LCB Tenders) elsewhere, those in the BEC / BRC shall prevail.

11.0 To ascertain the substantial responsiveness of the bid OIL reserves the right to ask the bidder for clarification in respect of clauses covered under BRC also and such clarifications fulfilling the BRC clauses in toto must be received on or before the deadline given by the company, failing which the offer will be summarily rejected.

12.0 Please do refer the User Manual provided on the portal on the procedure How to create Response for submitting offer.

NOTE:

Bidders should submit their bids (preferably in tabular form) explicitly mentioning compliance / non compliance to all the NIT terms and conditions of NIT.

Yours Faithfully

Sd-
MS A GOGOI
SENIOR MANAGER MATERIALS
FOR : GENERAL MANAGER (PLS)

Item srl no	Specification																																																					
10	The primer shall consist of a mixture of butyl rubber, synthetic compound and a solvent. The primer shall be applied to the appropriately prepared pipe surface before application of inner layer tape. The function of primer is to provide a bonding medium between the pipe surface and the inner layer tape. The primer shall be quick drying type; the maximum drying time shall not be more than 30 minutes. The primer shall be suitable for brush application as well as machine application. The coverage of the primer shall be 7sq.m per liter and the shelf life of the primer shall be 3 years. The primer shall comply with the requirement of latest DIN EN 12068 (stress class #C) Standard and shall be free from any health hazard during storage and application. The offered primer shall be compatible with the offered tape and shall be suitable for application at temperature ranging from 0° C to 60° C and operation of the coated pipe from temperatures ranging from 0° C to 50° C. Dry film thickness of the primer shall be 40-80 microns. NOTE: THE PRIMER SHALL BE SUPPLIED IN GOOD QUALITY CONTAINERS OF 20-25 LITERS CAPACITY HAVING PROPER CAPING FACILITY. Material Safety Data Sheet shall be supplied with the primer. <table><tr><td rowspan="13">Primer</td><td>Properties</td><td>Unit</td><td>Value</td><td>Test Method</td></tr><tr><td>It shall consist of butyl rubber, synthetic compound and a solvent</td><td></td><td></td><td>DIN EN 12068</td></tr><tr><td>Colour</td><td></td><td>Black</td><td></td></tr><tr><td>Density</td><td>g/cc</td><td>>=0.78</td><td></td></tr><tr><td>Total solid contents</td><td>%</td><td>20-26</td><td></td></tr><tr><td>Coverage</td><td>Ltr/Sqm</td><td>0.14</td><td></td></tr><tr><td>Application Temperature</td><td>Deg C</td><td>30-60</td><td></td></tr><tr><td>Drying Time at 23 deg C</td><td>Minutes</td><td>30 min</td><td></td></tr><tr><td>Brush and manual application</td><td></td><td></td><td></td></tr><tr><td>Shelf Life</td><td>Years</td><td>3</td><td></td></tr><tr><td>Dry film thickness of primer</td><td>micron</td><td>40-80</td><td></td></tr><tr><td>Container capacity</td><td>Liters</td><td>20-25</td><td></td></tr><tr><td colspan="4">Material Safety Data sheet shall be supplied</td></tr></table>	Primer	Properties	Unit	Value	Test Method	It shall consist of butyl rubber, synthetic compound and a solvent			DIN EN 12068	Colour		Black		Density	g/cc	>=0.78		Total solid contents	%	20-26		Coverage	Ltr/Sqm	0.14		Application Temperature	Deg C	30-60		Drying Time at 23 deg C	Minutes	30 min		Brush and manual application				Shelf Life	Years	3		Dry film thickness of primer	micron	40-80		Container capacity	Liters	20-25		Material Safety Data sheet shall be supplied			
Primer	Properties		Unit	Value	Test Method																																																	
	It shall consist of butyl rubber, synthetic compound and a solvent				DIN EN 12068																																																	
	Colour			Black																																																		
	Density		g/cc	>=0.78																																																		
	Total solid contents		%	20-26																																																		
	Coverage		Ltr/Sqm	0.14																																																		
	Application Temperature		Deg C	30-60																																																		
	Drying Time at 23 deg C		Minutes	30 min																																																		
	Brush and manual application																																																					
	Shelf Life		Years	3																																																		
	Dry film thickness of primer		micron	40-80																																																		
	Container capacity		Liters	20-25																																																		
	Material Safety Data sheet shall be supplied																																																					
20	The tape shall be Co-Extruded Polyethylene Tape suitable for cold application OR Extruded hot calendared Polyethylene tape suitable for cold application. The inner tape shall have the butyl rubber adhesive on both sides and the outer tape shall have butyl rubber adhesive on one side only. A non-sticking separator strip (release film) shall be provided in the rolls to eliminate sticking of adhesive when the tape is in roll form.The consistency of the adhesive layer shall be such that under tension it flows on uneven steel surfaces. The adhesive layer shall be completely compatible with the properties of the primer. The inner tape must be self-amalgamating with the inner layer of outer Tape. It shall be standard product of the supplier having established history of excellent performance. PROPERTIES: The physical properties of the tape shall be as given below :- <table><tr><td></td><td colspan="4"></td></tr><tr><td rowspan="7"></td><td>Application Temperature</td><td>Deg C</td><td>0-60</td><td></td></tr><tr><td>Operating Temperature</td><td>Deg C</td><td>0-50</td><td></td></tr><tr><td>Total coating Thickness</td><td>mm</td><td>2.5-3.0</td><td>ASTM G-12</td></tr><tr><td>Thickness of Inner Layer Tape</td><td></td><td></td><td>ASTM D1000</td></tr><tr><td>Thickness of adhesive facing the steel pipe</td><td>mm</td><td>0.178</td><td></td></tr><tr><td>Thickness of backing (carrier film)</td><td>mm</td><td>0.305</td><td></td></tr><tr><td>Thickness of adhesive facing the outer layer Tape</td><td>mm</td><td>0.152</td><td></td></tr></table>							Application Temperature	Deg C	0-60		Operating Temperature	Deg C	0-50		Total coating Thickness	mm	2.5-3.0	ASTM G-12	Thickness of Inner Layer Tape			ASTM D1000	Thickness of adhesive facing the steel pipe	mm	0.178		Thickness of backing (carrier film)	mm	0.305		Thickness of adhesive facing the outer layer Tape	mm	0.152																				
	Application Temperature	Deg C	0-60																																																			
	Operating Temperature	Deg C	0-50																																																			
	Total coating Thickness	mm	2.5-3.0	ASTM G-12																																																		
	Thickness of Inner Layer Tape			ASTM D1000																																																		
	Thickness of adhesive facing the steel pipe	mm	0.178																																																			
	Thickness of backing (carrier film)	mm	0.305																																																			
	Thickness of adhesive facing the outer layer Tape	mm	0.152																																																			

		Total thickness	mm	0.635	
		Thickness of outer Layer Tape			
		Thickness of adhesive facing the inner layer Tape	mm	0.305	
		Thickness of backing (carrier film)	mm	0.33	
		Total thickness	mm	0.635	
		width of tape	mm	100	
		Deviation in width		1.5	
		Impact resistance (10 impacts at least)		No holiday with a test voltage of 15 kV	DIN EN 12068 Annexure H
		Indentation resistance pressure (test condition)			DIN EN 12068 Annexure G
		at 23 deg C	N/mm2	10	
		at 50 deg C	N/mm2	10	
		Remaining Thickness	mm	0.6(min)	
		Holiday Detection		Pass	
		Thermal ageing resistance			
		Ratio of tape strength		$1.25 \geq S_{100}/S_0 \geq 0.75$ $S_{100}/S_{70} \geq 0.8$	
		Ratio of bursting strength		$1.25 \geq B_{100}/B_0 \geq 0.75$ $B_{100}/B_{70} \geq 0.8$	
		Elongation at break		$1.25 \geq E_{100}/E_0 \geq 0.75$ $E_{100}/E_{70} \geq 0.8$	
		Peel strength layer to layer		$P_{100}/P_0 \geq 0.75$ $P_{100}/P_{70} \geq 0.8$	
		Peel strength to pipe surface		$P_{100}/P_0 \geq 0.75$ $P_{100}/P_{70} \geq 0.8$	
		Specific electrical wrapping resistance	Ohm-m2		DIN EN 12068, Annex-J
		RS100		10^8	
		RS100/RS70		>0.8	
		Cathodic Disbondment at 23 deg C	mm	15(max)	DIN EN 12068, Annex-K
		Adhesion strength at 23 deg C			
		Inner layer to primed pipe	N/mm	0.75 (min)	DIN EN 12068, Annex-C
		Inner layer to existing CTE/3LPE/Coal Tar Tape coatings	N/mm	0.4 (min)	
		Layer to Layer			
		Inner to Inner + outer to Inner	N/mm	1.5 (min)	DIN EN 12068, Annex-B
		Outer to Outer	N/mm	0.2 (min)	
		Adhesion strength at 50 deg C			
		Inner layer to primed pipe	N/mm	0.075 (min)	DIN EN 12068, Annex-C
		Inner layer to existing CTE/3LPE/Coal Tar Tape coatings	N/mm	0.04 (min)	
		Layer to Layer			
		Inner to Inner + outer to Inner	N/mm	0.2 (min)	DIN EN 12068, Annex-B
		Outer to Outer	N/mm	0.2 (min)	

	<table><tr><td>LAP shears strength between wrapping and metal surface of existing coating @ 50 deg C</td><td>N/mm2</td><td>0.05(min)</td><td>DIN EN 12068, Annex-D</td></tr><tr><td>Shelf life</td><td>years</td><td>5(min)</td><td></td></tr><tr><td>Storage temperature</td><td>Deg C</td><td>0-50</td><td></td></tr></table>	LAP shears strength between wrapping and metal surface of existing coating @ 50 deg C	N/mm2	0.05(min)	DIN EN 12068, Annex-D	Shelf life	years	5(min)		Storage temperature	Deg C	0-50												
LAP shears strength between wrapping and metal surface of existing coating @ 50 deg C	N/mm2	0.05(min)	DIN EN 12068, Annex-D																					
Shelf life	years	5(min)																						
Storage temperature	Deg C	0-50																						
	Tapes to be provided in Rolls of 30 m each for Inner and Outer wrap.																							
30	The Mastic Compound shall be in the form of Putty Filler. The mastic compound shall be suitable filling the irregularities on pipe surface and in areas around weld reinforcements prior to wrapping with anti- corrosion tapes and shall be suitable for molding around irregular profiles such as flanges, mechanical joints and valves to provide a contour suitable for wrapping with anti-corrosion tapes. It shall be compatible with primer consisting of a mixture of butyl rubber, synthetic compound and a solvent normally used with cold applied coating tapes. It shall have high electrical corrosion resistance to protect API quality steel pipe and pipe fittings even without an overlaying coating tape and shall have excellent Cathodic disbondment characteristics and normal temperature. The Mastic compound shall be suitable for cold application in a wide range of climatic conditions. The Mastic compound shall be self-supporting for sealing, filling and caulking applications where protective, waterproof and non-setting mastic is required. COMPOSITION: Petrolatum compound containing inert siliceous fillers and vegetable fibers. It should not contain any volatile organic solvents. <table><tr><th><u>TYPICAL PROPERTIES</u></th><th><u>DATA</u></th></tr><tr><td>Colour</td><td>Green/Brown</td></tr><tr><td>Specific Gravity</td><td>1.39</td></tr><tr><td>Specific Volume</td><td>720 cm3/kg</td></tr><tr><td>Flash Point</td><td>>180°C</td></tr><tr><td>Temperature Range</td><td>0°C to 70°C</td></tr><tr><td>For Application</td><td>90°C maximum</td></tr><tr><td>For Service</td><td>API quality hydrocarbon, transportation pipe and pipe fittings 3kg Blocks</td></tr><tr><td>PACKING</td><td>Extruded Rounds Strips 330mm long x50mm diameter And /or Extruded Triangular Strips 330mm long x 50mm x 50mm x 70mm</td></tr><tr><td>RECOMMENDED PRIMER</td><td>Compatible with primer consisting of a mixture of butyl rubber, synthetic compound and a solvent normally used with cold applied coating tapes. Where required use Primer.</td></tr></table>				<u>TYPICAL PROPERTIES</u>	<u>DATA</u>	Colour	Green/Brown	Specific Gravity	1.39	Specific Volume	720 cm3/kg	Flash Point	>180°C	Temperature Range	0°C to 70°C	For Application	90°C maximum	For Service	API quality hydrocarbon, transportation pipe and pipe fittings 3kg Blocks	PACKING	Extruded Rounds Strips 330mm long x50mm diameter And /or Extruded Triangular Strips 330mm long x 50mm x 50mm x 70mm	RECOMMENDED PRIMER	Compatible with primer consisting of a mixture of butyl rubber, synthetic compound and a solvent normally used with cold applied coating tapes. Where required use Primer.
<u>TYPICAL PROPERTIES</u>	<u>DATA</u>																							
Colour	Green/Brown																							
Specific Gravity	1.39																							
Specific Volume	720 cm3/kg																							
Flash Point	>180°C																							
Temperature Range	0°C to 70°C																							
For Application	90°C maximum																							
For Service	API quality hydrocarbon, transportation pipe and pipe fittings 3kg Blocks																							
PACKING	Extruded Rounds Strips 330mm long x50mm diameter And /or Extruded Triangular Strips 330mm long x 50mm x 50mm x 70mm																							
RECOMMENDED PRIMER	Compatible with primer consisting of a mixture of butyl rubber, synthetic compound and a solvent normally used with cold applied coating tapes. Where required use Primer.																							
40	HAND WRAPPING TOOL FOR COLD APPLIED TAPE COAT.																							

Note to the bidders:

- 1.0 **All the items will be procured from same source.**
- 2.0 Material 99072975 (item no 20) shall have consist of 3 ply / 2 ply tape coat system comprising of 3 ply inner wrap & 2 ply outer wrap and **the quantity will be 55000 roll each.**
- 3.0 **Testing and Inspection :**

All the properties mentioned in the specification shall be tested at manufacturer's works place with their in house test facilities as per applicable standard. The testing shall be witnessed by OIL approved Third party Inspection Agency (TPI) viz LLOYDS / RITES/IRS/BV and DNV . OIL representative may witness the test carried out by TPI . The supplier shall submit the copy of test certificates duly witnessed and endorsed by OIL approved Third party inspection agency.

Charges, if any ,shall be quoted separately as per **Annexure-I(A)** and the same shall be considered for bid evaluation. **In case, TPI charge is NIL/inclusive, bidder must categorically mention the same in their offer .**

4.0 In the event of an order,

i) **Marking** : Following shall be clearly marked on the containers of the primer, tape & filler material in ENGLISH.

TYPE / TRADE NAME

WIDTH; LENGTH OF THE TAPE IN METRIC UNIT /

VOLUME OF PRIMER WEIGHT OF PUTTY FILLER REFERENCE NUMBER / BATCH NUMBER

MANUFACTURING DATE, SHELF LIFE OF TAPE / PRIMER.

HEALTH HAZARDS ASSOCIATED

& HANDLING INSTRUCTION.

ii) **Packaging** :All material shall be supplied in unit quantities, which can be easily handled by the applicators. The packaging shall be such that during transportation and storage at owner's stores and subsequent transportation and handling at site, full quantity and performance of the material is retained.

iii) **Data to be Furnished** : The supplier shall submit the following information along the supplied material.

a) Maximum exposure time of applied tape before backfilling.

b) Recommended time lag (Maximum and Minimum) between application of primer and Tape.

c). Application procedure of the tape system i.e. primer, inner wrap & Outer wrap.

4.0 Application Guideline: Tape shall be able to give adequate adhesion to steel when applied over pipe surface prepared up to a level of St 2/st. Application of the primer over the pipe shall ensure adequate adhesion to the pipe surface.

Supplier to provide all technical details, application procedure and guidelines for use of coating system along with the supply of materials along with the BID document / offer. Detailed instructions for application of tape as well as the primer by hand application / machine application shall be indicated clearly.

5.0. The supplier shall provide assistance in demonstrating the proper method of application of coating system as required by OIL. During initial application supplier shall depute his representative / applicator to demonstrate / guide the field applicator so that allocated material i.e. primer, inner tape, outer tape, filler material etc is applied as per material guidelines to achieve the desired properties / protection of pipeline. The supplier may have to carry out demonstration at 3 / 4 locations for an extra length of 1000 - 1500 M.

Charges, if any ,shall be quoted separately as per **Annexure I(A)** and the same shall be considered for bid evaluation. **In case Demonstration charge is NIL/inclusive, bidder must categorically mention the same in their offer.**

6.0 Compatibility of Environment:

The coating system to be supplied shall be compatible with the environment and shall be suitable for application in RoW having soil of varied characteristics.

7.0 Material Safety Data Sheet [MSDS] to be provided.

Bid Rejection Criteria (BRC) & Bid Evaluation Criteria (BEC)

The following BRC/BEC will govern the evaluation of the bids received against this tender. Bids that do not comply with stipulated BRC/BEC in full will be treated as non responsive and such bids shall prima-facie be rejected. Bid evaluation will be done only for those bids that pass through the “Bid Rejection Criteria” as stipulated in this document.

Other terms and conditions of the enquiry shall be as per General Terms and Conditions vide MM/LOCAL/E-01/2005 for E-Procurement LCB Tenders. However, if any of the Clauses of the Bid Rejection Criteria / Bid Evaluation Criteria (BRC / BEC) contradict the Clauses of the tender or MM/LOCAL/E-01/2005 elsewhere, those in the BRC / BEC shall prevail.

(A) Technical

1.1.1 Bidder shall be either a manufacturer or a supplier, authorized by manufacturer of the materials as quoted for. The quoted materials shall conform to as per specifications and applicable/ relevant Codes or standards.

1.1.2 The bidder must have experience of supplying the specified material and/or similar material for coating of cross-country hydrocarbon pipelines of minimum length 500 inch km (Pipe size in inch X length of pipeline in KM) conforming to applicable/ relevant Codes or standards during last 7(Seven) years ending bid closing date.

1.1.3 In case the bidder is a manufacturer:

1.1.3.1 The manufacturer shall be a regular manufacturer of the materials of same brand as quoted for.

1.1.3.2 The manufacturer shall have manufactured and supplied the materials of offered type since last ten years reckoned from the date of commencement of sale of bidding document.

1.1.4 In case the bidder is a supplier, authorized by the manufacturer, the following criteria shall be met by the bidder:

1.1.4.1 The bidder shall supply the materials produced by an established manufacturer, who meets the qualification requirements stipulated under clauses 1.1.1 to 1.1.3.2.

1.1.4.2 The bidder shall furnish an authority certificate from the manufacturer, confirming the bidder’s status as their authorized supplier. The authority certificate shall be valid up to the completion tenure of order as per the bid document.

1.1.4.3 The bidder shall furnish from the manufacturer a certificate to the effect that the manufacturer as a policy do not quote directly and their materials are quoted by authorized suppliers only.

1.1.4.4 One manufacturer can quote only through one supplier.

1.1.4.5 One supplier can quote based on an authority letter from one manufacturer only.

1.1.4.6 The bid shall be liable for rejection, incase of any change of the manufacturer for the aforesaid materials after submission of bid.

1.1.5 The manufacturer or Supplier shall furnish documentary evidence such as purchase order , inspection release note, completion certificate of relevant previous supplies / works , product catalogue, reference list of previous supplies and details of manufacturing , inspection & testing facilities at proposed mill(s) / coating plant(s) , as applicable , in support of meeting the above qualification criteria along with the bid otherwise the bid will be considered as non-responsive and hence rejected.

1.1.6 The bidder shall provide credential of offered materials in the form of performance certificate of satisfactory usage/ application of the materials in cross-country hydrocarbon pipelines since last 7 years from owner of hydrocarbon pipelines.

(B) COMMERCIAL :

i) Bids are invited under Single Stage Two Bid System. Bidders have to submit both the Unpriced Bids and Priced Bids through electronic form in the OIL’s e-Tender portal within the Bid closing date and time stipulated in the e-Tender. The unpriced bid is to be submitted as per scope of work and technical specification of the tender and the price bid as per the online commercial bid format. For details of submission procedure, please refer relevant para of general terms and conditions vide MM/LOCAL/E-01/2005 for E-procurement LCB tenders. Any offer not complying with the above shall be rejected straightway.

ii) Bid security:

Bid security of Rs 13,39, 000.00. shall be submitted manually in sealed envelope superscribed with Tender no. and Bid Closing date to Chief Manager(PL), Pipeline Headquarters, Oil India Limited, Guwahati- 781171, Assam on or before the Bid Closing Date and Time mentioned in the Tender. If bid security in ORIGINAL of above mentioned amount is not received within bid closing date and time , the bid submitted through electronic form will be rejected without any further consideration. For exemption for submission of Bid Security, please refer Clause No.

8.8 of General Terms and Conditions vide MM/LOCAL/E-01/2005 for E-Procurement LCB Tenders. **The Bid Security shall be valid for 10 months from the date of bid opening (i.e. upto 09/11/2014).**

In case of extension of Bid Closing date against the tender where a bidder has already submitted his bid with requisite bid security validity within the original B.C. Date such bidders will extend validity of bid security covering the extended period of the bid closing date.

iii) Performance Bank Guarantee:

Successful bidder will be required to furnish a Performance Bank Guarantee @10% of the order value.

For exemption for submission of Performance Bank Guarantee, please refer Clause No. 9.12 of General Terms and Conditions vide MM/LOCAL/E-01/2005 for E-Procurement LCB Tenders. The Performance Bank Guarantee for capital nature items like plant and machinery etc. shall be valid for 12 months from the date of commissioning or 18 months from the date of despatch whichever concludes earlier. However, for consumables like chemicals, cement, tubular etc. the Performance Bank Guarantee shall be valid for 12 months from the date of despatch.

iv) The Bank Guarantee should be allowed to be encashed at all branches within India.

v) Validity of the bid shall be minimum 120 days from the Bid Closing Date.

vi) The prices offered will have to be firm through delivery and not subject to variation on any account. A bid submitted with an adjustable price will be treated as non-responsive and rejected.

vii) Bids received after the bid closing date and time will be rejected. Similarly, modifications to bids received after the bid closing date & time will not be considered.

viii) All the Bids must be Digitally Signed using #Class 3# digital certificate (e-commerce application) as per Indian IT Act obtained from the licensed Certifying Authorities operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India. The bid signed using other than #Class 3# digital certificate, will be rejected.

ix) C folder is meant for Technical bid only. Therefore, No price should be given in C folder, otherwise the offer will be rejected.

x) Price should be maintained in the "online price schedule" only. The price submitted other than the "online price schedule" shall not be considered.

xi) The User ID & Password are not transferable. Bids submitted by parties to whom the User ID & Password was not issued by the Company will be rejected.

xii) Conditional offers will be rejected.

xiii) Bids received in any form or media other than through OIL's e-Procurement portal will not be accepted.

xiv) Bid documents uploaded in the e-Procurement Portal shall be typed/written and scanned clearly and contain no inter lineation, erasures or overwriting except as necessary to correct errors made by bidder. Any bid not meeting this requirement shall be rejected.

xv) Bidders must quote clearly and strictly in accordance with the price schedule outlined in #Price Schedule Format# (Annexure-5) of bidding documents, otherwise the bid will be summarily rejected. The Bids in which the rates for any part of the work are not quoted shall be rejected.

xvi) Bidder must accept and comply with the following clauses as given in the Bidding Document in toto, failing which offer will be rejected.

a. Performance Bank Guarantee clause

b. Force Majeure clause

c. Tax liabilities clause

d. Arbitration clause

e. Applicable Law

f. Liquidated Damage clause

xvii). Integrity Pact:

OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide Annexure DDD of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be returned by the bidder (along with the technical bid) duly signed (digitally) by the same signatory who signed the bid, i.e., who is duly authorized to sign the bid. Any bid not accompanied by Integrity Pact Proforma duly signed (digitally) by the bidder shall be rejected straightway. Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact has been signed by the bidder's authorized signatory who sign the Bid.

ii) If any of the clauses in the BRC contradicts with other clauses of bidding document elsewhere, then the clauses in the BRC shall prevail.

2.0 BID EVALUATION CRITERIA (BEC):

A. TECHNICAL:

i) All the items will be procured from the same source. Evaluation will be done taking the prices of all items together .

ii) The bids confirming the specifications, term and conditions stipulated in the enquiry and considered to be responsive after subjecting to Bid Rejection Criteria will be considered for further evaluation as per the Bid Evaluation Criteria.

B. COMMERCIAL:

i) To evaluate the inter-se-ranking of the offers, Assam entry tax on purchase value will be loaded as per prevailing Govt. of Assam guidelines as applicable on bid closing date. Bidders may check this with the appropriate authority while submitting their offer.

ii) To ascertain the substantial responsiveness of the bid OIL reserves the right to ask the bidder for clarification in respect of clauses covered under BRC also and such clarifications fulfilling the BRC clauses in toto must be received on or before the dead line given by the company, failing which the offer will be summarily rejected.

iii) Price bids of only those bidders will be opened whose offers are found technically acceptable. The technically acceptable bidders will be informed before opening of the “price bid”.
